

407 – 15216 North Bluff Road White Rock, BC Canada V4B 0A7 Phone: 604.424.9092 Toll Free: 1.877.352.9158 Fax: 1.877.453.0658 Email: info@microedgeinstruments.com Web: www.microedgeinstruments.com





Product Description

SHT11 RH & Temperature Sensor Probe consists of a SHT11 digital RH & Temperature sensor from Sensirion and a sintered copper protection housing. It is used to measure ambient relative humidity and temperature, the data can be transferred to host device via I2C communications. It works with any device supporting I2C comm. interface.

Applications of SHT11 Sensor Probe:


- High Accurate Relative Humidity and Temperature Measurement
- Hursh Industrial Environment
- Space limited area

Specifications

Product Identification	
Product Name	SHT11 RH & Temperature Sensor Probe
Model	ASHT-11
Internal Sensors	
Manufacturer	Sensirion
Manufacturer Model	SHT11
Channels	Relative humidity ($0 \sim 100\%$ RH)
	Temperature ($-40^{\circ}C \sim 70^{\circ}C$, $-40^{\circ}F \sim 158^{\circ}F$)
Resolution	Temperature: 12-bit
	Relative Humidity: 12-bit
Accuracy	Temperature: +/- 0.4°C at 25°C
	Relative Humidity: +/-3% (20% ~ 80% RH)
Source Voltage	2.4 to 5.5 VDC, Typical: 3.3 VDC
Communication	Digital 2-wire interface: I2C
Physical	
Length	Three feet
Protection Housing	Sintered copper
Connection	Four open wires: Power, Ground, SCK, Data
Others	
Operating Environment	$-40 \sim +70^{\circ}$ C (-40° F ~ 158°F), 0~95%RH non-condensing.

Please refer to Sensirion for detailed specifications of SHT11 sensor.

Dimension:



Pin-out:

Color	Name
Yellow	SCK
Red	VDD
Green	GND
Blue	Data

Microedge Instruments Inc. 407 - 15216 North Bluff Road White Rock, BC, Canada, V4B 0A7